



Extended Life **FULL SYNTHETIC** **SAE 75W-90** **PREMIUM GEAR OIL**



MFA Oil Extended Life Full Synthetic SAE 75W-90 Premium Gear Oil is formulated with 100% synthetic base oils and provides superior gear protection over a wide range of operating and ambient temperatures. MFA Oil Extended Life Full Synthetic SAE 75W-90 Premium Gear Oil is formulated with premium extreme pressure additives, rust preventatives and anti-foam additives to protect hypoid gears, manual transmissions, gear boxes, passenger car and light truck conventional and limited slip differentials, transmissions and steering gears.

- Superior gear tooth wear protection
- Superior thermal and oxidative stability for high temperature operation
- Superior bearing corrosion protection
- Superior anti-foam characteristics
- Good seal compatibility
- Limited slip performance

Always follow manufacturer's guide for proper SAE grade and API classification.



Extended Life FULL SYNTHETIC SAE 75W-90 PREMIUM GEAR OIL



Typical Characteristics

PRODUCT	Full Syn 75W-90
Gravity, °API	33.32
Specific Gravity @ 60°F (15.6°C)	0.8585
Viscosity @ 40°C cSt	96.47
Viscosity @ 100°C cSt	14.53
Viscosity Index	156
Pour Point °C (°F)	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	60,000
Color	1

Performance Level

- API GL-5
- MT-1
- Mack GO-J, GO-H, GO-G
- MIL-PRF-2105E (J2360)
- AIST (formerly U.S. Steel 224)
- AGMA 9005-E0, 250.03, 250.04, 252.02, No. 4
- ArvinMeritor 076-E

Available In:

5 Gal, 16 Gal Keg, 55 Gal,

