



# *Full Strength* **ANTIFREEZE & COOLANT** LOW SILICATE



MFA Oil Low Silicate Antifreeze & Coolant is a premium quality, single phase, permanent-type engine coolant produced to exceed the requirements of modern automotive and diesel engines. The virgin materials in the formulation are specifically selected to give maximum protection for aluminum engines and heavy-duty diesel engines.

MFA Oil Low Silicate Antifreeze & Coolant provides protection from freezing, overheating, rust and corrosion for one full year when used as recommended. The inhibitor combination in MFA Oil Low Silicate Antifreeze & Coolant gives optimum protection to all system metals, even in areas where adverse conditions exist. Quality inhibitors and ethylene glycol base stocks enable this product to protect against the rust and corrosion of aluminum, cast iron, steel, solder, copper and brass. It won't harm plastic overflow tanks found in cooling systems or deteriorate radiator hose or gasket material. It offers exceptionally low foaming tendencies even when subjected to severe operating conditions, and it is water soluble in all concentrations to give uniform heat transfer and complete freeze protection.

- Universal formula for both automotive and diesel engines
- Optimum protection to all engine systems metals
- Exceptional low foaming characteristics
- Excellent anti-boil protection under heavy duty usage

*Always consult and follow manufacturer's guide for proper cooling system maintenance. Always follow diesel engine manufacturer's recommendations for use of supplemental coolant additives (SCA).*



# Full Strength ANTIFREEZE & COOLANT LOW SILICATE



## Typical Characteristics

PRODUCT	Full Strength AF
Color	Green
Flash Pt., °F	235° Min.
Specific Gravity 60°/60°F	1.110-1.145
Ash Content	5% Max
Reserve Alkalinity	10.0 Min.
PH@50% Vol. Solution	10.0 - 11.0
Silicon, PPM	250 Max
Color	1

## Performance Level

ASTM D-3306  
ASTM D-4985

## Available In:

1 Gal, 55 Gal, Bulk\*

\* Available by special request

