



Premium ATF AUTOMATIC TRANSMISSION FLUID

For Use Where DEXRON®-III or
MERCON® Fluid is Specified



MFA Oil Premium Automatic Transmission Fluid is blended using only high quality Group II, severely hydrocracked, high viscosity index, paraffinic base stocks and robust additive chemistry. It is formulated to meet the increased demands of today's automatic transmission vehicles operating under higher temperatures with reduced cooling capacity, higher fluid turnover rates and increased energy densities. This product meets or exceeds the DEXRON®-III-H enhanced formulation and represents a significant performance upgrade over the previous automatic transmission fluid.

MFA Oil Automatic Transmission Fluid meets GM® specification 6417M and is approved for use in all GM® cars with automatic transmissions. It is recommended for automatic transmissions in Chrysler and American Motors cars, except when the owner's manuals requires Type 7176 fluid, and approved for use in Ford vehicles where Mercon is recommended. It meets Ford's previous factory fill M2C138-CJ and M2C166-H specifications and also may be used in import vehicles when DEXRON®-III/MERCON® fluid is recommended.

MFA Oil Automatic Transmission Fluid meets requirements of Allison C-3/C-4 fluid and can be used in Allison power shift transmissions and other torque converter systems requiring this type of fluid.

This product is not intended for use in transmission final drives with wet-brake designs or as an engine crankcase oil.

- Superior oxidation resistance
- Enhanced friction durability
- Superior shifting performance
- Enhanced usable fluid life
- Enhanced seal compatibility
- Increased resistance to sludge
- Shear stability

Always follow manufacturer's guide for proper application.



Premium ATF AUTOMATIC TRANSMISSION FLUID

For Use Where DEXRON®-III or
MERCON® Fluid is Specified



Typical Characteristics

PRODUCT	ATF
Gravity, °API	32.73
Specific Gravity @ 60°F (15.6°C)	0.8616
Viscosity @ 40°C cSt	38.7
Viscosity @ 100°C cSt	7.55
Viscosity Index	167
Pour Point °C (°F)	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	18,700
Color	Red

Performance Level

DEXRON®-III/MERCON®
GENERAL MOTORS 6417M
FORD M2C138-CJ
ALLISON C3/C4
CATERPILLAR TO-2
DENISON HF-0
VICKERS 35VQ25
SUNSTRAND

Available In:

Qt, 2.5 Gal, 16 Gal Keg*, 30 Gal,
55 Gal, Bulk

* Available by special request

