



INDUSTRIAL EP GEAR OILS



Work Horse® Industrial EP Gear Oils are formulated using a combination of only high quality Group II, severely hydrocracked, high viscosity index, paraffinic base stocks, Group I solvent refined paraffinic base stocks and extreme pressure (EP) non-lead additives.

Work Horse Industrial EP Gear Oils are recommended for a wide variety of enclosed industrial gearing. It is designed to provide exceptional film strength with excellent load-carrying capacity and will withstand the severe shock loads and sliding velocities characteristic of industrial and mining operations.

- Superior load-carrying capacity
- Superior wear protection
- Superior thermal and oxidative stability
- Superior bearing corrosion protection

Always follow manufacturer's guide for proper SAE grade and API classification.

Work Horse is a new breed of lubricants designed to stand up to brutal workloads and a wide range of challenging conditions. Born from a 90-year legacy of proven performance and premium products, Work Horse lubricants are formulated using the latest technology and advanced additives to deliver superior results and the protection you demand. Extensive testing in both on-road and off-road environments ensures all Work Horse products meet and exceed major manufacturers' service requirements. Your hard-working equipment needs hard-working oil.



INDUSTRIAL EP GEAR OILS

Typical Characteristics

PRODUCT	ISO 150	ISO 220	ISO 320
Gravity, °API	29.75	28.91	28.22
Specific Gravity @ 60°F (15.6°C)	0.8775	0.8821	0.8859
Viscosity @ 40°C cSt	157.8	227.3	340.1
Viscosity @ 100°C cSt	16.12	20.1	25.73
Viscosity Index	106	102	99
Pour Point °C (°F)	-27°C (-17°F)	-24°C (-11°F)	-15°C (5°F)
Color	3	3.5	3.5
Phosphorus, wt. %	0.013	0.013	0.013
Sulfur, wt. %	0.336	0.336	0.336



Performance Level

ISO 12925-1 TYPE CKC

U.S. STEEL 224

AGMA 9005 D-94, 250.04, 251.02

AGMA 9005-E02

DIN 51517 PART 3

API GL-2

CINCINNATI MACHINE/MILACRON

GENERAL MOTORS LS-2

Available In:

5 Gal*, 55 Gal Drum, Bulk.

* Available by special request