

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

1. Identification

Product identifier used on the label: WORK HORSE GEAR OIL SAE 80W-90 420068, 420069, 420070, 420071, 420072

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Gear Oil

Restrictions on use: Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

MFA Oil Company

importer, or other responsible party:

One Ray Young Drive

Columbia, MO 65201

Phone number: (800) 827-0116

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Hazardous to the aquatic environment - Acute Category 2

Hazard Statements: Toxic to aquatic life

Precautionary Statements:

Prevention: Avoid release to the environment.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulations.

Hazards not otherwise classified: No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Petroleum distillates, solvent dewaxed heavy paraffinic	No data available	64742-65-0	10 - 30
Petroleum distillates, solvent- refined heavy paraffinic	No data available		0.1 - 1
Amines, C12-14-tert-alkyl	No data available	68955-53-3	0.1 - 1

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen.

Eye Contact: Immediately flush eyes with plenty of water for at least 20 minutes

retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder.

Get medical attention if irritation develops or persists. Remove

contaminated clothing and continue flushing with water.

Ingestion: Do not induce vomiting and seek medical attention immediately. Provide

medical care provider with this SDS.

Most important symptoms/effects,

acute and delayed:

Indication of immediate medical attention and special treatment

needed, if necessary:

No additional first aid information available.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

No data available

Hazardous combustion products: Nitrogen containing gases, Carbon dioxide, Carbon monoxide, Sulfur

containing gases, Aldehydes, oxides of phosphorus, Hydrogen sulfide,

Smoke

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid release to the environment.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling:

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well-ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer. Follow all protective equipment recommendations provided in Section 8.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Acids, Oxidizing materials

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Petroleum distillates,	5 mg/m3	5 mg/m3	10 mg/m3	No data available
hydrotreated heavy				
paraffinic				

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

Petroleum distillates,	5 mg/m3	5 mg/m3	10 mg/m3	No data available
solvent dewaxed heavy				
paraffinic				

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

Respirator Type(s):None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Eye protection: Wear chemically resistant safety glasses with side shields when handling

this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact

lenses. Have an eye wash station available.

Skin protection: Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Gloves: Neoprene, Nitrile

General hygiene conditions: Follow all protective equipment recommendations provided in Section 8.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Brown
Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:

No data available

Freezing point:

No data available

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

Flash Point (°C): 232

Evaporation Rate:No data available **Flammability (solid, gas):**No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Not established

Lower flammability or explosive

limits:

Not established

Vapor pressure: No data available Vapor density: No data available

Relative density: 0.88

Solubility(ies):

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

No data available

No data available

No data available

Not determined

Viscosity: 152.7

10. Stability and reactivity

Reactivity: There are no known reactivity hazards associated with this product.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None expected under standard conditions of storage.

Conditions to avoid (e.g., static discharge, shock, or vibration):

Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.

Moisture (will lead to product performance degradation).

Incompatible materials: Acids, Oxidizing materials

Hazardous decomposition products: Nitrogen containing gases, Carbon dioxide, Carbon monoxide, Sulfur

containing gases, Aldehydes, oxides of phosphorus, Hydrogen sulfide,

Smoke

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

Skin contact, Inhalation, Ingestion, Eye contact

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

and eye contact):

Symptoms related to the physical,

chemical and toxicological

characteristics:

No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion: No hazard in normal industrial use. Estimated to be > 5.0 g/kg.

Skin Contact: This material is likely to be moderately irritating to skin based on animal

data. Can cause moderate skin irritation, defatting, and dermatitis. Not

likely to cause permanent damage.

Absorption: Estimated to be > 5.0 g/kg; practically non-toxic

Inhalation: No hazard in normal industrial use. Likely to be practically non-toxic

based on animal data.

Eye Contact: This material is likely to be severely irritating to eyes based on animal

data. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or

blurred vision) is possible.

Sensitization: Non-hazardous under Respiratory Sensitization category. Contains

a substance that may cause skin sensitization.

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: None known.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Amines, C12-14-tert-alkyl	Oral LD50 Rat 300 mg/kg	Dermal LD50 Rat 251 mg/kg	
Petroleum distillates,	Oral LD50 Rat > 15000	Dermal LD50 Rabbit > 5000	Inhalation LC50 (4h) Rat =

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

solvent dewaxed heavy	mg/kg	mg/kg	2.18 mg/L
paraffinic			

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability: Biodegrades slowly.

Bioaccumulative potential: Bioconcentration may occur.

Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as hazardous to the ozone layer):

None known.

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Dispose of contents and container in accordance with local/regional/national/international regulations.

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

Contaminated packaging: Containers of this material may be hazardous when emptied.

Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:No data available

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

Environmental hazards (e.g., Marine

pollutant (Yes/No)):

None.

Transport in bulk (according to Annex II

of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the US TSCA Inventory or are

exempt.

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

Regulated Components:

Chemical Name	CAS#	CERCLA	Sara EHS	Sara 313	U.S. HAP
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	N	N	N	N
Amines, C12-14-tert- alkyl	68955-53-3	N	N	N	N

Chemical Name	CAS#	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	N	N	N	N
Amines, C12-14-tert- alkyl	68955-53-3	N	N	N	N

Chemical Name	CAS#	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N	Z
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	N	N	N	N	N
Amines, C12-14-tert- alkyl	68955-53-3	N	N	N	N	N

16. Other information, including date of preparation or last revision.

SDS Prepared by: TPRUETT

WORK HORSE GEAR OIL SAE 80W-90

Stock Number: 420068, 420069, 420070, 420071, 420072

Revision Date: 07-08-2019

Replaces:

Revision Date: 07-08-2019

Revision Number: 4

Reason for revision:NEW VERSIONReferences:No data availableOther Info:No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.