

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

. Identification	
Product identifier used on the label: Stock Number:	WORK HORSE GEAR OIL 85W-140 420073, 420074
Other means of identification:	
Synonyms:	No data available
Recommended use of the chemical and re Recommended use:	e strictions on use: Gear Oil
Restrictions on use:	Uses other than those described above
Name, address, and telephone number	MFA Oil Company
of the chemical manufacturer, importer, or other responsible party:	One Ray Young Drive
	Columbia, MO 65201
Phone number:	(800) 827-0116
E-mail address:	sds@wd-wpp.com
Emergency phone number:	CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification:	Hazardous to the aquatic environment - Acute Category 2
Hazard Statements:	Toxic to aquatic life
Precautionary Statements: Prevention:	Avoid release to the environment.
Disposal:	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazards not otherwise classified:	No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Petroleum distillates, solvent dewaxed heavy paraffinic	No data available	64742-65-0	80 - 100
Petroleum distillates, solvent- refined heavy paraffinic	No data available		0.1 - 1
Amines, C12-14-tert-alkyl	No data available	68955-53-3	0.1 - 1

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen.
Eye Contact:	Immediately flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Remove contaminated clothing and continue flushing with water.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS.
Most important symptoms/effects, acute and delayed:	
Indication of immediate medical attention and special treatment needed, if necessary:	No additional first aid information available.

5. Fire-fighting	measures
------------------	----------

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Unsuitable extinguishing media:	No data available
Specific hazards arising from the chemical:	No data available
Hazardous combustion products:	Nitrogen containing gases, Carbon dioxide, Carbon monoxide, Smoke, Sulfur containing gases, Aldehydes, oxides of phosphorus, Hydrogen sulfide

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

Special protective equipment and precautions for fire-fighters:	Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures:	Avoid release to the environment.
Methods and materials for containment and cleaning up:	Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations. Used fluid should be disposed of at a recycling center.
7. Handling and storage	
Precautions for safe handling:	Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well-ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer. Follow all protective equipment recommendations provided in Section 8.
Conditions for safe storage, including any incompatibilities:	
Safe storage conditions:	Store in a cool dry place. Isolate from incompatible materials.
Materials to Avoid/Chemical	Acids, Oxidizing materials

8. Exposure controls/personal protection

Incompatibility:

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Petroleum distillates, solvent dewaxed heavy paraffinic	5 mg/m3	5 mg/m3	10 mg/m3	No data available
Petroleum distillates, hydrotreated heavy	5 mg/m3	5 mg/m3	10 mg/m3	No data available

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

paraffinic		
Appropriate engineering controls:	Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.	
Individual protection measures, such a	as personal protective equipment:	
Respiratory Protection:	Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.	
Respirator Type(s):	None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.	
Eye protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact lenses. Have an eye wash station available.	
Skin protection:	Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.	
Gloves:	Neoprene, Nitrile	
General hygiene conditions:	Follow all protective equipment recommendations provided in Section 8.	

9. Physical and chemical properties

Appearance (physical state, color etc.):	
Physical state:	Liquid
Color:	Brown
Odor:	Mild
Odor Threshold:	Not determined
pH:	No data available
Melting point/freezing point:	
Melting Point:	No data available
Freezing point:	No data available
Flash Point (°C):	265

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

Evaporation Rate:	No data available
Flammability (solid, gas):	No data available
Upper/lower flammability or explosive limits:	
Upper flammability or explosive limits:	Not established
Lower flammability or explosive limits:	Not established
Vapor pressure:	No data available
Vapor density:	No data available
Relative density:	0.9
Solubility(ies):	Negligible; 0-1%
Partition coefficient: n-octanol/water:	No data available
Auto-ignition temperature:	No data available
Decomposition Temperature:	Not determined
Viscosity:	388.7

10. Stability and reactivity

2	
Reactivity:	There are no known reactivity hazards associated with this product.
Chemical stability:	Stable under normal conditions.
Possibility of hazardous reactions:	None expected under standard conditions of storage.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Moisture (will lead to product performance degradation).
Incompatible materials:	Acids, Oxidizing materials
Hazardous decomposition products:	Nitrogen containing gases, Carbon dioxide, Carbon monoxide, Smoke, Sulfur containing gases, Aldehydes, oxides of phosphorus, Hydrogen sulfide

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of
exposure (inhalation, ingestion, skin
and eye contact):Skin contact, Inhalation, Ingestion, Eye contact

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

Symptoms related to the physical, chemical and toxicological characteristics:	No data available
Delayed and immediate effects and also c	hronic effects from short- and long-term exposure:
Ingestion:	No hazard in normal industrial use. Estimated to be > 5.0 g/kg.
Skin Contact:	This material is likely to be moderately irritating to skin based on animal data. Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Absorption:	Likely to be practically non-toxic based on animal data.
Inhalation:	No hazard in normal industrial use. Likely to be practically non-toxic based on animal data.
Eye Contact:	This material is likely to be severely irritating to eyes based on animal data. Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in tearing and reddening, but not likely to permanently injure eye tissue. Temporary vision impairment (cloudy or blurred vision) is possible.
Sensitization:	Non-hazardous under Respiratory Sensitization category. Contains a substance that may cause skin sensitization.
Mutagenicity:	No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.
Carcinogenicity:	Not expected to cause cancer. This product meets the IP-346 criteria of <3% PAH's and is not considered a carcinogen by the International Agency for Research on Cancer.
STOT-single exposure:	Based on available data, the classification criteria are not met.
STOT-repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.
Other information:	None known.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Amines, C12-14-tert-alkyl	Oral LD50 Rat 300 mg/kg	Dermal LD50 Rat 251 mg/kg	
Petroleum distillates, solvent dewaxed heavy	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat = 2.18 mg/L

WORK HORSE GEAR OIL 85W-140
Stock Number: 420073, 420074
Revision Date: 07-08-2019
Replaces:

paraffinic		

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability:	Biodegrades slowly.

Bioaccumulative potential:	Bioconcentration may occur.
Mobility in soil:	This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as None known. hazardous to the ozone layer):

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:	Dispose of contents and container in accordance with local/regional/national/international regulations.
Contaminated packaging:	Containers of this material may be hazardous when emptied.

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

Recycle containers whenever possible.

14. Transport information	
Carriage of dangerous goods by road (DC)T), rail or inland waterways:
DOT Basic Description:	No data available
International carriage of dangerous good	ls by sea (IMDG/IMO):
UN number:	Not regulated by IMDG
UN Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group, if applicable:	Not applicable
International carriage of dangerous good	ls by air (IATA):
UN number:	Not regulated by IATA
UN Proper shipping name:	Not applicable
Transport hazard class(es):	Not applicable
Packing group, if applicable:	Not applicable
Environmental hazards (e.g., Marine pollutant (Yes/No)):	None.
Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	No data available
Special precautions which a user needs to be aware of or needs to comply with in connection with transport or conveyance either within or outside their premises:	No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status:

All components of this material are on the US TSCA Inventory or are exempt.

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

Regulated Components:

Chemical Name	CAS #	CERCLA	Sara EHS	Sara 313	U.S. HAP
Petroleum distillates,					
solvent dewaxed	64742-65-0	Ν	N	Ν	N
heavy paraffinic					
Petroleum distillates,					
hydrotreated heavy	64742-54-7	Ν	N	Ν	N
paraffinic					
Amines, C12-14-tert-	68955-53-3	Ν	N	N	N
alkyl	08933-33-3	IN	IN	IN	IN

Chemical Name	CAS #	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Ν	N	Ν	N
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Ν	N	N	N
Amines, C12-14-tert- alkyl	68955-53-3	Ν	N	Ν	Ν

Chemical Name	CAS #	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Ν	Ν	Ν	Ν	Ν
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Ν	Ν	Ν	Ν	Ν
Amines, C12-14-tert- alkyl	68955-53-3	Ν	Ν	Ν	Ν	Ν

16. Other information, including date of preparation or last revision.

SDS Prepared by:

TPRUETT

WORK HORSE GEAR OIL 85W-140 Stock Number: 420073, 420074 Revision Date: 07-08-2019 Replaces:

Revision Date:

References:

Other Info:

Disclaimer:

Revision Number:

Reason for revision:

07-08-2019

4

NEW VERSION No data available No data available

This safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.