

WORK HORSE TORQUE FLUID TO-4 SAE30

Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

1. Identification

Product identifier used on the label: WORK HORSE TORQUE FLUID TO-4 SAE30

Stock Number: 420089, 420090, 420091, 420092

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use:

Transmission Fluid

Restrictions on use:Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

MFA Oil Company

in a surface of the surface of the second

One Ray Young Drive

importer, or other responsible party:

Columbia, MO 65201

Phone number: (800) 827-0116

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Hazardous to the aquatic environment - Acute Category 3

Hazardous to the aquatic environment - Chronic Category 3

Hazard Statements: Harmful to aquatic life; Harmful to aquatic life with long lasting effects

Precautionary Statements:

Prevention: Avoid release to the environment.

Disposal: Dispose of contents/container in accordance with

local/regional/national/international regulations.

Hazards not otherwise classified:No data available

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Petroleum distillates, solvent dewaxed heavy paraffinic	No data available	64742-65-0	0.1 - 1

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication

WORK HORSE TORQUE FLUID TO-4 SAE30 Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen.

Eye Contact: Use eye wash to remove a chemical from the eye. Flush the affected eye

for at least fifteen minutes. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Seek medical attention if

irritation persists.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or

persists. Seek medical advice if symptoms persist.

Ingestion: No hazard in normal industrial use. Do not induce vomiting. Seek medical

attention if symptoms develop. Provide medical care provider with this

SDS.

Most important symptoms/effects,

acute and delayed:

Indication of immediate medical attention and special treatment

needed, if necessary:

No additional first aid information available.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

No data available

Hazardous combustion products: Carbon monoxide, Sulfur containing gases, Nitrogen containing gases,

Aldehydes, oxides of phosphorus, Hydrogen sulfide, Smoke

Special protective equipment andDo not enter fire area without proper protection including self- contained

breathing apparatus and full protective equipment. Use methods for the

WORK HORSE TORQUE FLUID TO-4 SAE30 Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

precautions for fire-fighters: surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Avoid release to the environment.

Methods and materials for containment

and cleaning up:

No special spill clean-up considerations. Collect and discard in regular

trash.

7. Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure. Follow all

protective equipment recommendations provided in Section 8.

Conditions for safe storage, including

any incompatibilities:

Safe storage conditions: Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3	5 mg/m3	10 mg/m3	No data available
Highly refined synthetic base stocks	5 mg/m3	5 mg/m3	10 mg/m3	No data available
Petroleum distillates, solvent dewaxed heavy paraffinic	5 mg/m3	5 mg/m3	10 mg/m3	No data available

Appropriate engineering controls: Use local exhaust ventilation or other engineering controls to minimize

exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the

WORK HORSE TORQUE FLUID TO-4 SAE30 Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

preferred means of protection. Use a respirator if general room

ventilation is not available or sufficient to eliminate symptoms.

Respirator Type(s): None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Eye protection: No special requirements under normal industrial use.

Skin protection: Where use can result in skin contact, practice good personal hygiene and

wear impervious gloves. Wash hands and other exposed areas with mild

soap and water before eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile

General hygiene conditions: Follow all protective equipment recommendations provided in Section 8.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Brown
Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:No data availableFreezing point:No data available

Flash Point (°C): 215

Evaporation Rate:No data available **Flammability (solid, gas):**No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

= 10

limits:

Lower flammability or explosive

limits:

= 1

Vapor pressure: No data available Vapor density: No data available

WORK HORSE TORQUE FLUID TO-4 SAE30 Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

Relative density: 0.88

Solubility(ies): Negligible; 0-1% Partition coefficient: n-octanol/water: No data available **Auto-ignition temperature:** No data available **Decomposition Temperature:** Not determined

Viscosity: 101.1

10. Stability and reactivity

Reactivity: There are no known reactivity hazards associated with this product.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None expected under standard conditions of storage.

Conditions to avoid (e.g., static Temperatures above the high flash point of this combustible material in discharge, shock, or vibration):

combination with sparks, open flames, or other sources of ignition.

Moisture (will lead to product performance degradation).

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide, Sulfur containing gases, Nitrogen containing gases,

Aldehydes, oxides of phosphorus, Hydrogen sulfide, Smoke

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Skin contact, Inhalation, Ingestion, Eye contact

Symptoms related to the physical,

chemical and toxicological

characteristics:

No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion: No hazard in normal industrial use. Estimated to be > 5.0 g/kg.

Skin Contact: This material is likely to be slightly irritating to skin based on animal

data. Can cause minor skin irritation, defatting, and dermatitis.

Absorption: Estimated to be > 5.0 g/kg; practically non-toxic

Inhalation: No hazard in normal industrial use. Likely to be practically non-toxic

based on animal data.

WORK HORSE TORQUE FLUID TO-4 SAE30

Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

Eye Contact: This material is estimated to be non-irritating eyes (Draize score <15

[rabbits]). No hazard in normal industrial use.

Sensitization: Non-hazardous under Respiratory Sensitization category.

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

STOT-single exposure:

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Other information: None known.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Petroleum distillates, solvent dewaxed heavy paraffinic	Oral LD50 Rat > 15000 mg/kg	Dermal LD50 Rabbit > 5000 mg/kg	Inhalation LC50 (4h) Rat = 2.18 mg/L

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L
Highly refined synthetic	64742-54-7	Aquatic EC50 (48h)	No data available	Aquatic LC50 (96h)

WORK HORSE TORQUE FLUID TO-4 SAE30 Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

base stocks		Daphnia > 1000 mg/L		Rainbow Trout > 5000 mg/L
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability: Biodegrades slowly.

Bioaccumulative potential: Bioconcentration may occur.

Mobility in soil:This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as

hazardous to the ozone layer):

None known.

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

packaging:

Dispose of contents and container in accordance with local/regional/national/international regulations.

Contaminated packaging: Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:No data available

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name: Not applicable

WORK HORSE TORQUE FLUID TO-4 SAE30

Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

Transport hazard class(es): Not applicable Packing group, if applicable: Not applicable

Environmental hazards (e.g., Marine

pollutant (Yes/No)):

None.

poliutalit (165/140)).

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with

in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the US TSCA Inventory or are

exempt.

Regulated Components:

Chemical Name	CAS#	CERCLA	Sara EHS	Sara 313	U.S. HAP
Petroleum distillates,					
hydrotreated heavy	64742-54-7	N	N	N	N
paraffinic					
Highly refined	64742-54-7	N	N	N	N
synthetic base stocks	04742-34-7	IN	IN	IN	IN
Petroleum distillates,					
solvent dewaxed	64742-65-0	N	N	N	N
heavy paraffinic					

Chemical Name	CAS#	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N
Highly refined synthetic base stocks	64742-54-7	N	N	N	N
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	N	N	N	N

WORK HORSE TORQUE FLUID TO-4 SAE30 Stock Number: 420089, 420090, 420091, 420092

Revision Date: 07-08-2019

Replaces:

Chemical Name	CAS#	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N	N
Highly refined synthetic base stocks	64742-54-7	N	N	N	N	N
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	N	N	N	N	Z

16. Other information, including date of preparation or last revision.

SDS Prepared by: TPRUETT
Revision Date: 07-08-2019

Revision Number: 16

Reason for revision:NEW VERSIONReferences:No data availableOther Info:No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.