



## FULL SYNTHETIC SAE 75W-140

**GEAR OIL** 

Work Horse® Full Synthetic SAE 75W-140 Gear Oil is formulated with 100% synthetic base oils and provides superior gear protection over a wide range of operating and ambient temperatures. It is formulated with premium extreme pressure additives, rust preventatives and anti-foam additives to protect hypoid gears, manual transmissions, gear boxes, passenger car and light truck conventional and limited slip differentials, transmissions and steering gears.

- Superior gear tooth wear protection
- Outstanding thermal and oxidative stability for high temperature operation
- Superior bearing corrosion protection
- Exceptional anti-foam characteristics
- Good seal compatibility
- · Limited slip performance

Always follow manufacturer's guide for proper SAE grade and API classification.

Work Horse is a new breed of lubricants designed to stand up to brutal workloads and a wide range of challenging conditions. Born from a 90-year legacy of proven performance and premium products, Work Horse lubricants are formulated using the latest technology and advanced additives to deliver superior results and the protection you demand. Extensive testing in both on-road and off-road environments ensures all Work Horse products meet and exceed major manufacturers' service requirements. Your hard-working equipment needs hard-working oil.



## FULL SYNTHETIC SAE 75W-140

**GEAR OIL** 

## **Typical Characteristics**

PRODUCT	Full Synthetic 75W-140
Gravity, °API	34.31
Specific Gravity @ 60°F (15.6°C)	0.8534
Viscosity @ 40°C cSt	171.8
Viscosity @ 100°C cSt	27.64
Viscosity Index	200
Pour Point °C (°F)	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	127,000
Color	1



## **Performance Level**

FORD M2C192-A

API GL-5

MT-1

MACK GO-J, GO-H, GO-G

ARVINMERITOR (ROCKWELL INTERNATIONAL) 076-E

AIST/US STEEL 224

AGMA 9005-E02, 250.03, 250.04, 251.02, NO. 4

LIMITED SLIP

SAE J2360, MIL-2105E/F

Available In: 55 Gal Drum, Bulk\*.

\* Available by special request