





For Use Where DEXRON®-III or MERCON® Fluid is Specified

Work Horse® Automatic Transmission Fluid (ATF) is specially formulated using only premium lubricating oils and a technologically advanced additive system.

This high-quality product is suitable for use where DEXRON®-II, DEXRON®-III or MERCON® fluids are specified.

Engineered to extend transmission life and smooth operation, Work Horse ATF provides the following benefits:

- Excellent high and low temperature protection
- Stable friction properties for smooth and consistent shifting
- Excellent shear stability
- Outstanding resistance to wear, oxidation and varnish deposits

Do not use this product in General Motors vehicles after model year 2005 or Ford vehicles after model year 2006. Do not use this product in transmissions that specify Ford Type F, MERCON® V, MERCON® SP, MERCON® LV or GM DEXRON®-VI fluid.

Always follow manufacturer's guide for proper application.

Work Horse[™] is a new breed of lubricants designed to stand up to brutal workloads and a wide range of challenging conditions. Born from a 90-year legacy of proven performance and premium products, Work Horse lubricants are formulated using the latest technology and advanced additives to deliver superior results and the protection you demand. Extensive testing in both on-road and off-road environments ensures all Work Horse products meet and exceed major manufacturers' service requirements. Your hard-working equipment needs hard-working oil.





AUTOMATIC TRANSMISSION FLUID

For Use Where DEXRON®-III or MERCON® Fluid is Specified

Typical Characteristics

PRODUCT	ATF
Gravity, °API	33.42
Specific Gravity @ 60°F (15.6°C)	0.858
Viscosity @ 40°C cSt	34.99
Viscosity @ 100°C cSt	7.139
Viscosity Index	179
Pour Point °C (°F)	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	12,537
Color	Red



Performance Level

MEETS REQUIREMENTS:

DEXRON® III G/H, DEXRON® II, DEXRON®, AW1

MERCON®

FORD M2C138-CJ

SUITABLE FOR USE:

ALLISON C-4, C-3, C-2

ALLISON C-4,

CAT TO-2

MB 236.1, ALLISON V-730D

TYPE A

Available in:

Qt, 2.5 Gal, 55 Gal Drum, Bulk