

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 **Revision Date:** 07-09-2019

Replaces:

1. Identification

Product identifier used on the label: WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Lubricants and performance fluids for the automotive industry

Restrictions on use:Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

MFA Oil Company

importer, or other responsible party:

One Ray Young Drive

Columbia, MO 65201

Phone number: (800) 827-0116

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Not classified as hazardous under OSHA

Hazards not otherwise classified:No data available

3. Composition/information on ingredients

| Chemical Name | Common name and synonyms | CAS# | % |
|---|--------------------------|--------------|-------|
| Methacrylate copolymer | No data available | Confidential | 3 - 7 |
| Petroleum distillates, hydrotreated light paraffinic | No data available | 64742-55-8 | 1 - 5 |

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 **Revision Date: 07-09-2019**

Replaces:

Inhalation: Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen.

Flush eyes with plenty of water for at least 20 minutes retracting eyelids **Eye Contact:**

often. Tilt the head to prevent chemical from transferring to the

uncontaminated eye. Get immediate medical attention.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or

persists. Seek medical advice if symptoms persist.

Ingestion: Minimal risk of harm if swallowed. Do not induce vomiting. Seek medical

attention immediately. Provide medical care provider with this SDS.

Most important symptoms/effects,

acute and delayed:

Eye irritation

Indication of immediate medical attention and special treatment

needed, if necessary:

Aspiration during swallowing or vomiting may severely damage the lungs. If evacuation of stomach contents is necessary, use method least likely to

cause aspiration. Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

> fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

No data available

Hazardous combustion products: Carbon monoxide, Smoke

Special protective equipment and

precautions for fire-fighters:

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the

surrounding fire.

6. Accidental release measures

Personal precautions, protective

equipment and emergency procedures:

No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations

found in Section 8 of this SDS.

Methods and materials for containment

Prevent the spread of any spill to minimize harm to human health and

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 Revision Date: 07-09-2019

Replaces:

and cleaning up: the environment if safe to do so. Wear complete and proper personal

protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations.

Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling: Mildly irritating material. Avoid unnecessary exposure. Follow all

protective equipment recommendations provided in Section 8.

Conditions for safe storage, including

any incompatibilities:

Safe storage conditions: Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

| Chemical component | OSHA PEL | ACGIH TLV | ACGIH STEL | IDLH |
|--|----------|-----------|------------|-------------------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based | 5 mg/m3 | 5 mg/m3 | 10 mg/m3 | No data available |
| Highly refined synthetic base stocks | 5 mg/m3 | 5 mg/m3 | 10 mg/m3 | No data available |
| Petroleum distillates, hydrotreated light paraffinic | 5 mg/m3 | 5 mg/m3 | 10 mg/m3 | No data available |
| Petroleum distillates, hydrotreated heavy paraffinic | 5 mg/m3 | 5 mg/m3 | 10 mg/m3 | No data available |

Appropriate engineering controls: Use local exhaust ventilation or other engineering controls to minimize

exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 Revision Date: 07-09-2019

Replaces:

preferred means of protection. Use a respirator if general room

ventilation is not available or sufficient to eliminate symptoms.

Respirator Type(s): None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Eye protection: Wear chemically resistant safety glasses with side shields when handling

this product. Do not wear contact lenses.

Skin protection: Where use can result in skin contact, practice good personal hygiene and

wear impervious gloves. Wash hands and other exposed areas with mild

soap and water before eating, drinking, and when leaving work.

Gloves: Nitrile, Neoprene

General hygiene conditions: Follow all protective equipment recommendations provided in Section 8.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Brown
Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:No data availableFreezing point:No data available

Flash Point (°C): 215

Evaporation Rate:No data available **Flammability (solid, gas):**No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Not established

Lower flammability or explosive

limits:

Not established

Vapor pressure: No data available
Vapor density: No data available

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 Revision Date: 07-09-2019

Replaces:

Relative density: 0.85

Solubility(ies): Negligible; 0-1%

Partition coefficient: n-octanol/water: 3.9

Auto-ignition temperature: No data available

Decomposition Temperature: Not determined

Viscosity: 35.94

10. Stability and reactivity

Reactivity: There are no known reactivity hazards associated with this product.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: None expected under standard conditions of storage.

Conditions to avoid (e.g., static discharge, shock, or vibration):

Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.

Moisture (will lead to product performance degradation).

Incompatible materials: Strong oxidizing agents

Hazardous decomposition products: Carbon monoxide, Smoke

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Skin contact, Inhalation, Ingestion, Eye contact

Symptoms related to the physical, chemical and toxicological

characteristics:

Eye irritation No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion: No hazard in normal industrial use. Estimated to be > 5.0 g/kg.

Skin Contact: This material is likely to be slightly irritating to skin based on animal

data. Can cause minor skin irritation, defatting, and dermatitis.

Absorption: Likely to be practically non-toxic based on animal data.

Inhalation: No hazard in normal industrial use. Likely to be practically non-toxic

based on animal data.

Eye Contact: The material is likely to be moderately irritating to eyes based on animal

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 Revision Date: 07-09-2019

Replaces:

data. Can cause moderate irritation, tearing and reddening, but not likely

to permanently injure eye tissue.

Sensitization: Non-hazardous under Respiratory Sensitization category.

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

STOT-single exposure:

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Other information: None known.

Numerical measures of toxicity (such as acute toxicity estimates):

| Chemical Name LD50 Oral | | LD50 Dermal | LC50 Inhalation | |
|--|-------------------------------|------------------------------------|---|--|
| Petroleum distillates, hydrotreated light paraffinic | Oral LD50 Rat > 5000 mg/kg | Dermal LD50 Rabbit > 2000 mg/kg | Inhalation LC50 (4h) Rat = 3900 mg/L | |
| Methacrylate copolymer | Oral LD50 Rat > 2000 mg/kg | | | |

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

| Chemical Name | OSHA Carcinogen | IARC Carcinogen | NTP Carcinogen |
|----------------------------|-----------------|-----------------|----------------|
| There are no components | | | |
| that are known or reported | | | |
| to cause cancer. | | | |

12. Ecological information

Ecotoxicity (aquatic and terrestrial,

where available):

Slight ecological hazard. In high concentrations, this product may be

dangerous to plants and/or wildlife.

Ecological Toxicity Data:

| Chemical Name | CAS# | Aquatic EC50 Crustacea | Aquatic ERC50 Algae | Aquatic LC50 Fish |
|--|------------|-----------------------------------|------------------------|------------------------------------|
| Petroleum distillates, hydrotreated light | 64742-55-8 | Aquatic EC50 (48h) Daphnia > 1000 | No data available | Aquatic LC50 (96h) Rainbow Trout > |

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 Revision Date: 07-09-2019

Replaces:

| paraffinic | | mg/L | | 5000 mg/L |
|--|------------|--|-------------------|--|
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | Aquatic LC50 (48h) > 1000 mg/L | No data available | Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L |
| Highly refined synthetic base stocks | 64742-54-7 | Aquatic EC50 (48h) Daphnia > 1000 mg/L | No data available | Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L |
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based | 72623-87-1 | Aquatic EC50 (48h) Daphnia > 1000 mg/L | No data available | Aquatic LC50 (96h) > 5000 mg/L |

Persistence and degradability: Biodegrades slowly.

Bioaccumulative potential: Bioconcentration may occur.

Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as

hazardous to the ozone layer):

None known.

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

packaging:

Contaminated packaging:

Spent or discarded material is non-hazardous according to environmental regulations.

Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:No data available

International carriage of dangerous goods by sea (IMDG/IMO):

UN number: Not regulated by IMDG

UN Proper shipping name: Not applicable Transport hazard class(es): Not applicable

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 Revision Date: 07-09-2019

Replaces:

Packing group, if applicable: Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name: Not applicableTransport hazard class(es): Not applicablePacking group, if applicable: Not applicable

Environmental hazards (e.g., Marine

pollutant (Yes/No)):

None.

Transport in bulk (according to Annex II

of MARDOL 72 /70 and the IDC Code).

of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with

in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the US TSCA Inventory or are

exempt.

Regulated Components:

| Chemical Name | CAS# | CERCLA | Sara EHS | Sara 313 | U.S. HAP |
|------------------------|--------------|--------|----------|----------|----------|
| Lubricating oils | | | | | |
| (petroleum), C20-50, | 72623-87-1 | N | N | N | N |
| hydrotreated neutral | | | | | |
| oil-based | | | | | |
| Highly refined | 64742-54-7 | N | N | N | N |
| synthetic base stocks | | | | | |
| Methacrylate copolymer | Confidential | N | N | N | N |
| Petroleum distillates, | | | | | |
| hydrotreated light | 64742-55-8 | N | N | N | N |
| paraffinic | | | | | |
| Petroleum distillates, | 64742-54-7 | N | N | N | N |

Safety Data Sheet WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 **Revision Date: 07-09-2019**

Replaces:

| hydrotreated heavy | | | |
|--------------------|--|--|--|
| paraffinic | | | |

| Chemical Name | CAS# | California Prop 65 - Cancer | California Prop 65 - Dev. Toxicity | California Prop 65 - Reprod fem | California Prop 65 - Reprod male |
|---|--------------|--------------------------------|---------------------------------------|------------------------------------|-------------------------------------|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | 72623-87-1 | N | N | N | N |
| Highly refined synthetic base stocks | 64742-54-7 | N | N | N | N |
| Methacrylate copolymer | Confidential | N | N | N | N |
| Petroleum distillates, hydrotreated light paraffinic | 64742-55-8 | N | N | N | N |
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N |

| Chemical Name | CAS# | Massachusetts RTK List | New Jersey RTK List | Pennsylvania RTK List | Rhode Island RTK List | Minnesota Hazardous Substance List |
|---|--------------|---------------------------|------------------------|--------------------------|-----------------------------|---|
| Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based | 72623-87-1 | N | N | N | N | N |
| Highly refined synthetic base stocks | 64742-54-7 | N | N | N | N | N |
| Methacrylate copolymer | Confidential | N | N | N | N | N |
| Petroleum distillates, hydrotreated light paraffinic | 64742-55-8 | Y | N | N | N | N |
| Petroleum distillates, hydrotreated heavy paraffinic | 64742-54-7 | N | N | N | N | N |

WORK HORSE FULL SYNTHETIC CVT TRANSMISSION FLUID

Stock Number: 420042, 420043 Revision Date: 07-09-2019

Replaces:

16. Other information, including date of preparation or last revision.

SDS Prepared by: HAZEMS
Revision Date: 07-09-2019

Revision Number: 10

Reason for revision: Activated by Document Formulation Generation

References:

Other Info:

No data available
No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents.

No warranty is made, either expressed or implied.