



FULL SYNTHETIC CVT

**CONTINUOUSLY VARIABLE
TRANSMISSION FLUID**

Work Horse® Full Synthetic Continuously Variable Transmission (CVT) Fluid is specially formulated with a unique combination of full synthetic base stocks and technologically advanced additives designed for the demands of CVTs. This product is recommended for use in many belt or chain driven continuously variable transmissions and it is not a replacement for ATF.

Work Horse CVT Transmission Fluid is recommended for: Audi/VW: TL 521 80, G 052 180, TL 521 16, G 052 516; BMW Mini Cooper EZL 779, Dodge/Jeep/Chrysler NS-2/CVTF+4; Honda HMMF, HCF2; Hyundai/Kia CVTF; Mazda JWS 3320, Mercedes Benz 236.20; Mitsubishi CVTF-J1, CVTF-J4; Nissan NS-1, NS-2, NS-3; Punch EZL 799/EZL 799A; Subaru iCVT, eCVT, Lineartronic CVT and CVT II; Suzuki CVTF TC, NS-2, CVT Green 1; Toyota CVTF TC, CVTF FE

Always follow manufacturer's guide for proper application.

Work Horse is a new breed of lubricants designed to stand up to brutal workloads and a wide range of challenging conditions. Born from a 90-year legacy of proven performance and premium products, Work Horse lubricants are formulated using the latest technology and advanced additives to deliver superior results and the protection you demand. Extensive testing in both on-road and off-road environments ensures all Work Horse products meet and exceed major manufacturers' service requirements. Your hard-working equipment needs hard-working oil.



FULL SYNTHETIC CVT

CONTINUOUSLY VARIABLE
TRANSMISSION FLUID

Typical Characteristics

PRODUCT	Full Synthetic CVT
Gravity, °API	34.87
Specific Gravity @ 60°F (15.6°C)	0.8505
Viscosity @ 40°C cSt	34.41
Viscosity @ 100°C cSt	7.221
Viscosity Index	181
Pour Point °C (°F)	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	10,000
Color	Amber



Performance Level

AUDI/VW (TL 52180; G 052 180; G 052 516)

DAIHATSU AMIX CVTF-DC, DAIHATSU AMIX CVTF-DFE

HONDA (HMMF, HCF-2)

PUNCH EZL 799/EZL 799A

TOYOTA (TC, FE)

NISSAN (NS-1, NS-2, NS-3)

MITSUBISHI (CVTF-J1)

SUBARU ICVT, ECVT, LINEATRONIC CVT, CV TII, HIGH TORQUE

MAZDA CVTF 3320

MERCEDES BENZ CVT28/MB-APPROVAL 236.20

MINI COOPER (EZL 799/ EZL 799A/ZF CVT V1)

MITSUBISHI DIAQUEEN (CVTF-J1, CVTF-J4)

HYUNDAI/KIACVTF (SP-CVT 1, SP-III)

SUZUKI (TC / NS-2 / CVTF GREEN 1, CVTF GREEN 2, CVTF 3320)

DODGE / JEEP (NS-2 / CVTF+4/MOPAR CVT 4)

GM/SATURN (DEX-CVT, CVTF I-GREEN2)

FORD CFT30/WSS-M2C933-A /MOTORCRAFT XT-7-QCFT

SHELL GREEN 1V