



# FULL SYNTHETIC MULTI-VEHICLE **AUTOMATIC** **TRANSMISSION FLUID**

Work Horse® Full Synthetic Multi-Vehicle Automatic Transmission Fluid (ATF) is a balanced, advanced formula utilizing superior additive technology and premium base oil that help ensure peak performance of many automatic transmissions manufactured after 1983, including many foreign vehicles.

Work Horse Full Synthetic Multi-Vehicle ATF meets the performance requirements of DEXRON®, DEXRON®-II, DEXRON®-IIE, DEXRON®-III, DEXRON®-VI, MERCON®, MERCON® LV, TOYOTA T-IV, HONDA Z-1 and NISSAN MATIC-J. This product is recommended for use in applications specifying • Audi/VW: G 052 025, 052 162, 055 025, GUS 000 162 • Ford (except Mercon® SP, V, or Type F) • GM DEXRON®-III, II • Honda: DW-1, Z-1 • Hyundai/Kia/Mitsubishi: SP-II, SP-III, SP-IV • Mazda ATF M-III, MV, T-IV • Nissan: Matic-D, J, K, 402 • Subaru: ATF, ATF-HP • Toyota: WS, T-IV, T-III, T-II, and in many other transmissions.

*Always follow manufacturer's guide for proper application.*

Work Horse is a new breed of lubricants designed to stand up to brutal workloads and a wide range of challenging conditions. Born from a 90-year legacy of proven performance and premium products, Work Horse lubricants are formulated using the latest technology and advanced additives to deliver superior results and the protection you demand. Extensive testing in both on-road and off-road environments ensures all Work Horse products meet and exceed major manufacturers' service requirements. Your hard-working equipment needs hard-working oil.



# FULL SYNTHETIC MULTI-VEHICLE **AUTOMATIC** TRANSMISSION FLUID

## Typical Characteristics

PRODUCT	FULL SYNTHETIC MULTI-VEHICLE ATF
Gravity, °API	35.6
Specific Gravity @ 60°F (15.6°C)	0.8468
Viscosity @ 40°C cSt	28.56
Viscosity @ 100°C cSt	5.797
Viscosity Index	151
Pour Point °C (°F)	-51°C (-60°F)
Brookfield Viscosity at -40°C, cP	10,300
Color	Red

License # J-60490. Consult owner's manual for recommended use.



## Performance Level

- MOPAR AS 68 RC, JWS 3309
- FORD M2C138-CJ
- CAT TO-2
- ALLISON C-3
- TYPE A
- ALLISON C-4
- WARREN DISTRIBUTION RECOMMENDS THIS PRODUCT AS SUITABLE FOR USE IN APPLICATIONS SPECIFYING ALLISON TES-389
- DAEWOO LT 71141
- DAIHATSU AMMIX ATF D-II, D-III SP
- DEXRON VI (APPROVED BY BRAND)
- CHRYSLER 8 AND 9 SPEED TRANSMISSIONS, MOPAR 8 & 9 FLUID 68218925AA
- GMN10060 (MEETS REQUIREMENTS)
- AUDI G 052 025, 052 162, 055 025
- AUDI 5 HP LT71141, G 052162-A1/A2, G052 025 A2, 053 025 A2, 060 162, 055, 540
- ESSO 71141
- BMW JWS 3309, LA2634, ZF 5HP18FL, 5HP24, 5HP30, MINI
- BMW P/N 83 22 0 024 359, ETL-8072B
- BMW P/N 83 22 0 0246 922, ETL-7045E
- BMW P/N 83 22 0 403 249, ETL-8072B
- BMW P/N 83 22 9 407 765, LA 2634
- BMW P/N 83 22 9 407 807, LT 711 41
- BMW 7045E, LA2634, LT71141
- DEXRON III G/H, DEXRON II, DEXRON, AW1
- TYPE A FIAT T-VI, JWS 3309
- GM 9986195
- HINO BLUE RIBBON ATF
- HONDA DW-1, Z-1. 3.1
- VOLVO P/N 1161540-8
- HYUNDAI/KIA/MITSUBISHI DIAMOND SP-II AND SP-III, RED-1, SP-IV
- HYUNDAI/KIA SP-IV M, RR DEX-II/SP-II, JWS 3314, 9683, 04000090SG
- MITSUBISHI DIAQUEEN SK, AW, J2, J3, PA, ATF-MA1
- CHRYSLER AS68RC, DIAMOND SP-III
- CHRYSLER P/N 05127382AA, P/N 68043742AA SUITABLE FOR USE
- JASO M315-2013 1A, 1A-LV, 2A
- JWS 3309, ANY 3309
- M315-2004 JASO 1A, 2A
- MAN 339 TYPE Z1, Z2, V1