

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 Revision Date: 07-08-2019

Replaces:

1. Identification

Product identifier used on the label: WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Lubricants and performance fluids for the automotive industry

Restrictions on use:Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

importer, or other responsible party:

MFA Oil Company

One Ray Young Drive

Columbia, MO 65201

Phone number: (800) 827-0116

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:



GHS Classification: Specific Target Organ Systemic Toxicity (STOT) - Repeated Exposure

Category 2

Signal Word: Warning

Hazard Statements: May cause damage to organs through prolonged or repeated exposure

Precautionary Statements:

Prevention:Do not breathe dust/fume/gas/mist/vapors/spray.Response:Get medical advice/attention if you feel unwell.Disposal:Dispose of contents/container in accordance with

local/regional/national/international regulations.

Hazards not otherwise classified:No data available

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
N N-bis(2-Ethylhexyl)-ar-methyl-	No data available	94270-86-7	0.1 - 1
1H-benzotnazole-1-			
methanamine			

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation: This material does not present a hazard if inhaled. Remove individual to

fresh air after an airborne exposure if any symptoms develop, as a

precautionary measure.

Eye Contact: None expected to be needed, however, use an eye wash to remove a

chemical from your eye regardless of the level of hazard.

Skin Contact: Wash with soap and water. Remove contaminated clothing and launder.

Get medical attention if irritation develops or persists.

Ingestion: No hazard in normal industrial use. Do not induce vomiting. Seek medical

attention if symptoms develop. Provide medical care provider with this

SDS.

Most important symptoms/effects,

acute and delayed:

May cause damage to organs through prolonged or repeated exposure

Indication of immediate medical attention and special treatment

needed, if necessary:

Get medical advice/attention if you feel unwell.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

Unsuitable extinguishing media:

20

No data available

Specific hazards arising from the chemical:

No data available

Hazardous combustion products:

Carbon dioxide, Carbon monoxide

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the

surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to human health and the environment if safe to do so. Wear complete and proper personal protective equipment following the recommendation of Section 8 at a minimum. Dike with suitable absorbent material like granulated clay. Dispose of according to Federal, State, Local, or Provincial regulations.

Used fluid should be disposed of at a recycling center.

7. Handling and storage

Precautions for safe handling:

Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well-ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer. Follow all protective equipment recommendations provided in Section 8.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Lubricating oils	5 mg/m3	5 mg/m3	10 mg/m3	No data available
(petroleum), C20-50,				
hydrotreated neutral oil-				
based				

Appropriate engineering controls: No engineering controls are likely to be required to maintain operator

comfort under normal conditions of use.

Individual protection measures, such as personal protective equipment:

Respiratory Protection: Do not breathe dust/fume/gas/mist/vapors/spray.

Respirator Type(s): None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

Eye protection: No special requirements under normal industrial use.

Skin protection: Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Gloves: Nitrile

General hygiene conditions: Follow all protective equipment recommendations provided in Section 8.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Beige
Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:No data availableFreezing point:No data available

Flash Point (°C): 237

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date: 07-08-2019**

Replaces:

Evaporation Rate: No data available Flammability (solid, gas): No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Not established

Lower flammability or explosive

limits:

Not established

Vapor pressure: No data available No data available Vapor density:

Relative density: 0.85

Solubility(ies): Negligible; 0-1%

Partition coefficient: n-octanol/water: 3.9

Auto-ignition temperature: No data available **Decomposition Temperature:** Not determined

110.7 **Viscosity:**

10. Stability and reactivity

Reactivity: There are no known reactivity hazards associated with this product.

Stable under normal conditions. **Chemical stability:**

Possibility of hazardous reactions: None expected under standard conditions of storage.

Conditions to avoid (e.g., static Temperatures above the high flash point of this combustible material in discharge, shock, or vibration):

combination with sparks, open flames, or other sources of ignition.

Incompatible materials: Strong oxidizing agents

No data available **Hazardous decomposition products:**

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Skin contact

Symptoms related to the physical,

chemical and toxicological

characteristics:

May cause damage to organs through prolonged or repeated exposure

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion: No hazard in normal industrial use. Estimated to be > 5.0 g/kg.

Skin Contact: This material is likely to be moderately irritating to skin based on animal

data. Can cause moderate skin irritation, defatting, and dermatitis. Not

likely to cause permanent damage.

Absorption: Estimated to be > 5.0 g/kg; practically non-toxic

Inhalation: No hazard in normal industrial use. Likely to be practically non-toxic

based on animal data.

Eye Contact: This material is likely to be non-irritating to eyes based on animal data.

Sensitization: Non-hazardous under Respiratory Sensitization category. Contains

a substance that may cause skin sensitization.

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

Carcinogenicity: Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

STOT-single exposure: Based on available data, the classification criteria are not met.

STOT-repeated exposure: Classification has been based on toxicological information of the

components in Section 3.

Aspiration hazard: Based on available data, the classification criteria are not met.

Other information: None known.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
N N-bis(2-Ethylhexyl)-ar- methyl-1H-benzotnazole- 1-methanamine	Oral LD50 Rat 3313 mg/kg	Dermal LD50 Rabbit > 2000 mg/kg	

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available):

Slight ecological hazard. In high concentrations, this product may be dangerous to plants and/or wildlife.

Ecological Toxicity Data:

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
N N-bis(2-Ethylhexyl)-ar- methyl-1H-benzotnazole-1- methanamine	94270-86-7	2.05 mg/L	0.976 mg/L	Aquatic LC50 (96h) 1.3 mg/L
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil- based	72623-87-1	Aquatic EC50 (48h) Daphnia > 1000 mg/L	No data available	Aquatic LC50 (96h) > 5000 mg/L

Persistence and degradability: No data available

Bioaccumulative potential: Bioconcentration is not expected to occur.

Mobility in soil: This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as

hazardous to the ozone layer):

None known.

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

Dispose of contents and container in accordance with local/regional/national/international regulations.

packaging:

Contaminated packaging: Recycle containers whenever possible.

14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

DOT Basic Description:No data available

International carriage of dangerous goods by sea (IMDG/IMO):

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

UN number: Not regulated by IMDG

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

International carriage of dangerous goods by air (IATA):

UN number: Not regulated by IATA

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

Environmental hazards (e.g., Marine

pollutant (Yes/No)):

None.

Transport in bulk (according to Annex II

of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs

to be aware of or needs to comply with

in connection with transport or conveyance either within or outside

their premises:

No data available

15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

TSCA Status: All components of this material are on the US TSCA Inventory or are

exempt.

Regulated Components:

Chemical Name	CAS#	CERCLA	Sara EHS	Sara 313	U.S. HAP
Lubricating oils					
(petroleum), C20-50,	72623-87-1	N	N	N	N
hydrotreated neutral	/2023-0/-1	IN	IN	IN	IN
oil-based					
N N-bis(2-					
Ethylhexyl)-ar-					
methyl-1H-	94270-86-7	N	N	N	N
benzotnazole-1-					
methanamine					

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

Chemical Name	CAS#	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Lubricating oils (petroleum), C20-50,					
**	72623-87-1	N	N	N	N
hydrotreated neutral					
oil-based					
N N-bis(2-					
Ethylhexyl)-ar-					
methyl-1H-	94270-86-7	N	N	N	N
benzotnazole-1-					
methanamine					

Chemical Name	CAS#	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	N	N	N	N	N
N N-bis(2- Ethylhexyl)-ar- methyl-1H- benzotnazole-1- methanamine	94270-86-7	N	N	N	N	N

16. Other information, including date of preparation or last revision.

SDS Prepared by: TPRUETT
Revision Date: 07-08-2019

Revision Number: 9

Reason for revision:NEW VERSIONReferences:No data availableOther Info:No data available

Disclaimer: This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we

WORK HORSE FULL SYNTHETIC TRANSMISSION FLUID SAE 50

Stock Number: 420044, 420045 **Revision Date:** 07-08-2019

Replaces:

believe the information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.