




# FULL SYNTHETIC TRANSMISSION SAE 50



Always follow manufacturer's guide for proper SAE grade and API classification.

Work Horse is a new breed of lubricants designed to stand up to brutal workloads and a wide range of challenging conditions. Born from a 90-year legacy of proven performance and premium products, Work Horse lubricants are formulated using the latest technology and advanced additives to deliver superior results and the protection you demand. Extensive testing in both on-road and off-road environments ensures all Work Horse products meet and exceed major manufacturers' service requirements. Your hard-working equipment needs hard-working oil.



# FULL SYNTHETIC TRANSMISSION SAE 50

## **Typical Characteristics**

PRODUCT	Full Synthetic Transmission SAE 50
Gravity, °API	35.62
Specific Gravity @ 60°F (15.6°C)	0.8467
Viscosity @ 40°C cSt	110.7
Viscosity @ 100°C cSt	18.22
Viscosity Index	183
Pour Point °C (°F)	-39°C (-38°F)
Color	1.5



### **Performance Level**

API MT-1

NAVISTAR/INTERNATIONAL TMS 6816

**MACK TO-A PLUS** 

**ZF FREEDOMLINE** 

MERITOR 0-81

### Available In:

5 Gal, 55 Gal Drum, 330 Gal Tote\* and Bulk\*

\* Available by special request