



Air Cooled **2-CYCLE ENGINE OIL**



MFA Oil 2-Cycle Engine Oil is a premium lubricant formulated for two-stroke lawnmowers, chainsaws, weed eaters and other two-stroke or two-cycle air-cooled engines. This high quality detergent and ashless two-cycle engine oil was formulated to provide outstanding protection against scuffing and ring sticking while reducing spark fouling and piston and exhaust deposits. It can be used as a pre-mix, two-cycle oil or in oil injection systems. It features multiple mix ratios from 16:1 to 50:1 on fuel-to-oil mixing. Always follow the manufacturer's recommendation for proper fuel-to-oil mixing.

- Ashless formulation minimizes engine deposits
- Protects against ring sticking, piston and cylinder scuffing
- Resists rust and oxidation
- Mixes with direct injection or premix engine
- Suitable for unleaded gasoline and unleaded gasoline with up to 10% ethanol blends.

NMMA License Number – RL26080G



Air Cooled 2-CYCLE ENGINE OIL



Typical Characteristics

PRODUCT	2-Cycle
Gravity, °API	31.22
Specific Gravity @ 60°F (15.6°C)	0.8696
Viscosity @ 40°C cSt	51.58
Viscosity @ 100°C cSt	7.686
Viscosity Index	114
Pour Point °C (°F)	-18°C (0°F)
Color	Blue
Sulfated Ash, wt. %	<0.04

Available In:

8 oz

