

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

Replaces:

1. Identification

Product identifier used on the label: WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150

Stock Number: 420007

Other means of identification:

Synonyms: No data available

Recommended use of the chemical and restrictions on use:

Recommended use: Hydraulic Oil

**Restrictions on use:** Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

One Ray Young Drive

MFA Oil Company

importer, or other responsible party:

Columbia, MO 65201

**Phone number:** (800) 827-0116

E-mail address: sds@wd-wpp.com

Emergency phone number: CHEMTREC: +1 (800) 424-9300 International: +01 (703) 527-3887

### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Classification: Not classified as hazardous under OSHA

**Hazards not otherwise classified:**No data available

#### 3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%	
Amines, C12-14-tert-alkyl	No data available	68955-53-3	0.1 - 1	

One or more hazardous ingredient(s) is claimed as a trade secret under the OSHA Hazard Communication Standard. The hazards of this (these) ingredient(s) are given on this SDS.

#### 4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

**Inhalation:** Remove to fresh air. If breathing is difficult, have a trained individual

administer oxygen.

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

**Replaces:** 

**Eye Contact:** None expected to be needed, however, use an eye wash to remove a

chemical from your eye regardless of the level of hazard.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or

persists.

**Ingestion:** No hazard in normal industrial use. Do not induce vomiting. Seek medical

attention if symptoms develop. Provide medical care provider with this

SDS.

Most important symptoms/effects,

acute and delayed:

Indication of immediate medical attention and special treatment

needed, if necessary:

No additional first aid information available.

### 5. Fire-fighting measures

#### Suitable (and unsuitable) extinguishing media:

**Suitable extinguishing media:** Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting

fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the

fire. Do not direct a stream of water into the hot burning liquid.

Unsuitable extinguishing media: No data available

Specific hazards arising from the

chemical:

No data available

Hazardous combustion products: Nitrogen containing gases, Carbon dioxide, Carbon monoxide, Smoke

Special protective equipment and

precautions for fire-fighters:

Do not enter fire area without proper protection including self- contained breathing apparatus and full protective equipment. Use methods for the

surrounding fire.

#### 6. Accidental release measures

Personal precautions, protective

equipment and emergency procedures:

No health affects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations

found in Section 8 of this SDS.

Methods and materials for containment

and cleaning up:

No special spill clean-up considerations. Collect and discard in regular

trash.

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

**Replaces:** 

7. Handling and storage

**Precautions for safe handling:** Mildly irritating material. Avoid unnecessary exposure. Follow all

protective equipment recommendations provided in Section 8.

Conditions for safe storage, including

any incompatibilities:

**Safe storage conditions:** Store in a cool dry place. Isolate from incompatible materials.

**Materials to Avoid/Chemical** 

Incompatibility:

Acids, Oxidizing materials

### 8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Petroleum distillates, hydrotreated heavy paraffinic	5 mg/m3	5 mg/m3	10 mg/m3	No data available

**Appropriate engineering controls:** 

Use local exhaust ventilation or other engineering controls to minimize

exposures and maintain operator comfort.

Individual protection measures, such as personal protective equipment:

**Respiratory Protection:** Respiratory protection may be required to avoid overexposure when

handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

**Respirator Type(s):** None required where adequate ventilation is provided. If airborne

concentrations are above the applicable exposure limits, use

NIOSH/MSHA approved respiratory protection.

**Eye protection:** No special requirements under normal industrial use.

**Skin protection:** Where use can result in skin contact, practice good personal hygiene and

wear impervious gloves. Wash hands and other exposed areas with mild

soap and water before eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile

**General hygiene conditions:** Follow all protective equipment recommendations provided in Section 8.

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

Replaces:

### 9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid
Color: Brown
Odor: Mild

Odor Threshold: Not determined PH: No data available

Melting point/freezing point:

Melting Point:

No data available

Freezing point:

No data available

Flash Point (°C): 232

**Evaporation Rate:** No data available **Flammability (solid, gas):** No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive

limits:

Lower flammability or explosive

limits:

Not established

Not established

Vapor pressure:No data availableVapor density:No data available

Relative density: 0.88

Solubility(ies):Negligible; 0-1%Partition coefficient: n-octanol/water:No data availableAuto-ignition temperature:No data availableDecomposition Temperature:Not determined

Viscosity: 157.8

### 10. Stability and reactivity

**Reactivity:** There are no known reactivity hazards associated with this product.

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous reactions:** None expected under standard conditions of storage.

**Conditions to avoid (e.g., static**Temperatures above the high flash point of this combustible material in

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

**Replaces:** 

**discharge, shock, or vibration):** combination with sparks, open flames, or other sources of ignition.

Moisture (will lead to product performance degradation).

**Incompatible materials:** Acids, Oxidizing materials

Hazardous decomposition products: Nitrogen containing gases, Carbon dioxide, Carbon monoxide, Smoke

### 11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Skin contact, Inhalation, Ingestion, Eye contact

Symptoms related to the physical,

chemical and toxicological

characteristics:

No data available

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion: No hazard in normal industrial use. Estimated to be > 5.0 g/kg.

**Skin Contact:** Likely to be non-irritating to skin based on animal data. Can cause

minor skin irritation, defatting, and dermatitis.

**Absorption:** Likely to be practically non-toxic based on animal data.

**Inhalation:** No hazard in normal industrial use. Likely to be practically non-toxic

based on animal data.

**Eye Contact:** This material is likely to be non-irritating to eyes based on animal data.

Sensitization: Non-hazardous under Respiratory Sensitization category.

Mutagenicity: No data available to indicate product or any components present at

greater than 0.1% is mutagenic or genotoxic.

**Carcinogenicity:** Not expected to cause cancer. This product meets the IP-346 criteria of

<3% PAH's and is not considered a carcinogen by the International

Agency for Research on Cancer.

STOT-single exposure:

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Other information: None known.

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

**Replaces:** 

#### Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Amines, C12-14-tert-alkyl	Oral LD50 Rat 300 mg/kg	Dermal LD50 Rat 251 mg/kg	

Is the hazardous chemical is listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
There are no components			
that are known or reported			
to cause cancer.			

### 12. Ecological information

Ecotoxicity (aquatic and terrestrial,

where available):

Slight ecological hazard. In high concentrations, this product may be dangerous to plants and/or wildlife.

#### **Ecological Toxicity Data:**

Chemical Name	CAS#	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	Aquatic LC50 (48h) > 1000 mg/L	No data available	Aquatic LC50 (96h) Rainbow Trout > 5000 mg/L

Persistence and degradability: Biodegrades slowly.

**Bioaccumulative potential:** Bioconcentration may occur.

**Mobility in soil:** This material is expected to have essentially no mobility in soil. It absorbs

strongly to most soil types.

Other adverse effects (such as

hazardous to the ozone layer):

None known.

#### 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:

Spent or discarded material is non-hazardous according to environmental regulations.

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

**Replaces:** 

**Contaminated packaging:** Recycle containers whenever possible.

### 14. Transport information

Carriage of dangerous goods by road (DOT), rail or inland waterways:

**DOT Basic Description:**No data available

International carriage of dangerous goods by sea (IMDG/IMO):

**UN number:** Not regulated by IMDG

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

International carriage of dangerous goods by air (IATA):

**UN number:** Not regulated by IATA

UN Proper shipping name:

Transport hazard class(es):

Packing group, if applicable:

Not applicable

Not applicable

**Environmental hazards (e.g., Marine** 

pollutant (Yes/No)):

None.

Transport in bulk (according to Annex II

of MARPOL 73/78 and the IBC Code):

No data available

Special precautions which a user needs to be aware of or needs to comply with

in connection with transport or conveyance either within or outside

their premises:

No data available

### 15. Regulatory information

Safety, health and environmental regulations specific for the product in question:

**TSCA Status:** All components of this material are on the US TSCA Inventory or are

exempt.

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

Replaces:

### **Regulated Components:**

Chemical Name	CAS#	CERCLA	Sara EHS	Sara 313	U.S. HAP
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N
Amines, C12-14-tert- alkyl	68955-53-3	N	N	N	N

Chemical Name	CAS#	California Prop 65 - Cancer	California Prop 65 - Dev. Toxicity	California Prop 65 - Reprod fem	California Prop 65 - Reprod male
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	Z
Amines, C12-14-tert- alkyl	68955-53-3	N	N	N	N

Chemical Name	CAS#	Massachusetts RTK List	New Jersey RTK List	Pennsylvania RTK List	Rhode Island RTK List	Minnesota Hazardous Substance List
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	N	N	N	N	N
Amines, C12-14-tert- alkyl	68955-53-3	N	N	N	N	N

### 16. Other information, including date of preparation or last revision.

SDS Prepared by: TPRUETT
Revision Date: 07-08-2019

Revision Number: 13

Reason for revision:NEW VERSIONReferences:No data availableOther Info:No data available

**Disclaimer:** This safety data sheet and the information it contains is offered to you in

good faith as accurate. We have reviewed any information contained in

**WORK HORSE INDUSTRIAL EP GEAR OIL ISO 150** 

Stock Number: 420007 Revision Date: 07-08-2019

Replaces:

the data sheet which we have received from outside sources and we believe the information to be correct but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.